

**ASTM E648 TESTING  
FOR  
QUANTUM TECHNICAL  
ON  
MTI RAIL FLOOR  
VTEC #100-5376-6  
TESTED: NOVEMBER 22, 2016**



# VTEC Laboratories Inc.

November 23, 2016

**Client:** Quantum Technical  
15 Riel Drive  
St. Albert, AB T8N 3Z2 CANADA

**Attention:** Mr. Tony LaGrange

**SUBJECT:**

Standard Test Method for Critical Radiant Flux of Floor-Covering Systems Using a Radiant Heat Energy Source according to ASTM E648 specification.

**DISCLAIMER:**

This is a factual report of the results obtained from the laboratory test of sample products. The results may be applied only to the products tested and should not be construed as applicable to other similar products of the manufacturer. The report is not a recommendation or a disapprobation by VTEC Laboratories Inc., of the material tested. While this report may be used for obtaining product acceptance, it may not be used in advertising.

**NOTICE:** VTEC Laboratories Inc., will not be liable for any loss or damage resulting from the use of the data in this report, in excess of the invoice. This report pertains to the sample tested only. Such report shall not be interpreted to be a warranty, either expressed or implied as to the suitability or fitness of said sample for such uses or applications, as the party contracting for the report may apply such sample.

**Material Tested:**

1) Product Description:	MTI Bus Floor
2) Supplier:	Quantum Technical
3) Specimen Composition:	Coated on metal
4) Average Thickness:	0.244 in.
5) Color:	Grey
6) Method of Mounting:	Self-supporting
7) Flux Profile Date:	11/17/16
8) Days in Conditioning:	10

**Test Results:**

	Sample #1	Sample #2	Sample #3
1) Specimen preheat Time (mins)	5:00	5:00	5:00
2) Initial Chamber Temperature (°C)	129	128	129
3) Total Burn Length (cm)	5.0	5.9	5.0
4) Time to Maximum Burn Length (min)	10.13	10.11	10.18
<u>5) Critical Radiant Flux (W/cm<sup>2</sup>)</u>	<b>0.94</b>	<b>0.93</b>	<b>0.94</b>
6) Average Critical Radiant Flux (W/cm <sup>2</sup> )	0.93		
7) Standard Deviation	0.00		
8) Coefficient of Variation (%)	0.42		

**Observations:**

Blistering during the 5:00 preheat



Neil Schultz  
Executive Director



Amirudin Rahim  
Technical Director